

427/Alrv SERIES

All metal medium to heavy duty profiles

For use in
hospitals • airports • shopping centres • rail stations
• sport stadiums • car parks • factories




Features:

- Attractive finish
- Solid aluminium construction
- Good anti-slip and cleaning properties due to a 'corrugated' style finish rather than a 'grooved' finish as found on alternative systems.
- Multi-directional movement:
Vertical, Horizontal and longitudinal
- Standard 4 metre lengths
- Floor to wall options
- Ability to mix leg heights to accommodate differing screed depths


Installation:

Laid on to epoxy mortar levelling bed, nominal 10mm deep and mechanically fixed symmetrically at 300mm centres, with M8 x 110mm resin anchor fixing or M10 concrete self tapping type bolt



Floor to wall options available

| Profile reference | 427/Alrv-040 | 427/Alrv-065 | 427/Alrv-100 |
|--------------------------------|---------------|-----------------|-----------------|
| Fb - Joint widths upto (mm) | 40mm | 65mm | 100mm |
| H - Heights (mm) | 32 & 45.5 mm | 32 & 45.5 mm | 32 & 45.5 mm |
| B - Overall width (mm) | 197mm | 228mm | 265mm |
| S - Visible width (mm) | 97mm | 128mm | 165mm |
| Accommodation of movement (mm) | 10mm (+/-5mm) | 20mm (+/- 10mm) | 30mm (+/- 15mm) |
| Material | Aluminium | Aluminium | Aluminium |
| Load Bearing capacity (kN) | 90kN 70kN | 35kN 35kN | 25kN 25kN |



Movement Joints (UK) Ltd,
Unit 3, 57 Thorby Avenue, March, Cambridgeshire PE15 0AZ United Kingdom
Tel: 01354 60 79 60 Fax: 01354 60 78 33
Web: www.mjuk.co.uk e-mail: info@mjuk.co.uk

IMPORTANT: Whilst all reasonable care is taken in compiling technical data on the company's products, all recommendations or suggestions regarding the use of such products are made without guarantee since the conditions of use are beyond the company. It is the customers responsibility to satisfy himself that each product is fit for the purpose for which he intends to use it and that the actual conditions of use are suitable.