





Movement Joints (UK)

P O Box 10, Wisbech,
Cambridgeshire PE13 4AN
Tel: 01945 450736 Fax: 01945 450819
Web: www.mjuk.co.uk
e-mail: info@mjuk.co.uk

428 Floor Series

Stainless Steel and Nitriflex®



Profile Number	428/d-030	428/d-050
Fb - Joint widths up to (mm)	30	50
H - Height (mm)	20 / 35 / 45 / 50 / 55 / 60	
B - Overall width (mm)	130	150
S - Visible width (mm)	30	50
Accommodation of movement (mm)	10 (+/- 5mm)	20 (+/-10mm)
Insert Colours	Black, grey	
Material	Stainless steel and Nitriflex®	
Standard Length (m)	3	
Load Bearing capacity (kN)	 35 kN  90 kN	

Applications: For all finishes (Screed, natural stone, cast stone etc)

Profile characteristics High resistance to corrosive media, interchangeable insert, attractive design, (smooth finish insert option)

Profile installation: See tips for planning and installation

IMPORTANT

Whilst all reasonable care is taken in compiling technical data on the company's products, all recommendations or suggestions regarding the use of such products are made without guarantee since the conditions of use are beyond the company. It is the customers responsibility to satisfy himself that each product is fit for the purpose for which he intends to use it and that the actual conditions of use are suitable.

