



446/Tn (3) SERIES

Surface fixed floor profile
 For use with vinyl flooring in
 hospitals • airports • shopping centres • schools




Features:

- Attractive finish
- Suitable for post fix installation
- aluminium construction with Nitriflex rubber insert
- Insert colours: black or grey. Alternative RAL coloured inserts are available - minimum order quantity applies.
- Smooth insert option available for laboratories and hospital wards (note: smooth insert reduces movement, contact us for further details).
- Possible to weld high quality vinyl floor covering to the central insert to give a sealed floor finish. Options of a raised insert for use with carpet.
- Standard 4 metre lengths
- Floor to wall options












Floor to wall options available



Optional: raised inserts of 5mm for carpet floor covering, see 446/Tn (5) data sheet

Note: smooth insert/seal options available for clean rooms, with reduced movement rating. Profiles are specified with suffix 'S' after code e.g. 446/Tn-030 (3) S Grey Insert.

Profile reference	446/Tn-020 (3)	446/Tn-030 (3)	446/Tn-050 (3)	446/Tn-065 (3)
Fb - Joint widths upto (mm)	20mm	30mm	50mm	65mm
H - Heights (mm)	20mm	29mm	29mm	29mm
B - Overall width (mm)	120mm	150mm	175mm	185mm
S - Visible width (mm)	20mm	30mm	50mm	65mm
Accommodation of movement (mm)	5 (+/-2.5mm)	10mm (+/- 5mm)	14mm (+/- 7mm)	20mm (+/- 10mm)
Material	Aluminium & Nitriflex	Aluminium & Nitriflex	Aluminium & Nitriflex	Aluminium & Nitriflex
Load Bearing capacity (kN)	 	 	 	 



Movement Joints (UK) Ltd,
 Unit 3, 57 Thorby Avenue, March, Cambridgeshire PE15 0AZ United Kingdom
 Tel: 01354 60 79 60 Fax: 01354 60 78 33
 Web: www.mjuk.co.uk e-mail: info@mjuk.co.uk

IMPORTANT: Whilst all reasonable care is taken in compiling technical data on the company's products, all recommendations or suggestions regarding the use of such products are made without guarantee since the conditions of use are beyond the company. It is the customers responsibility to satisfy himself that each product is fit for the purpose for which he intends to use it and that the actual conditions of use are suitable.