

446/a & 446/b SERIES

aluminium & rubber insert floor profile


For use in
hospitals • airports • shopping centres • schools

Features:

- Attractive finish
- aluminium construction with Nitriflex rubber insert
- Insert colours: black or grey. Alternative RAL coloured inserts are available - minimum order quantity applies.
- Smooth insert option available for laboratories and hospital wards (note: smooth insert reduces movement, contact us for further details).
- Options of a raised insert for use with vinyl or carpet to give a 'hidden' appearance
- Standard 4 metre lengths
- Floor to wall options

Installation:


Laid on to epoxy mortar levelling bed, nominal 10mm deep and mechanically fixed symmetrically at 300mm centres, with M8 x 110mm resin anchor fixing or M10 concrete self tapping type bolt




Floor to wall options available

Optional: raised inserts of 3mm for use with vinyl 446/Ta (3) and 446/Tb (3) or 5mm for carpet floor covering, 446/Ta (5) and 446/Tb (5)

Note: 446/Tb (3) series, a smooth insert/seal options available for clean rooms, with reduced movement rating. Profiles are specified with suffix 'S' after code e.g. 446/Tb-030 (3) S Grey Insert, height 60mm



Profile reference	446/a-020	446/b-030	446/b-050	446/b-065
Fb - Joint widths upto (mm)	20mm	30mm	50mm	65mm
H - Heights (mm)	20 & 35 mm	15, 20, 26, 35 or 50 mm	20, 26, 35, 50, 65, 80 mm	20, 26, 35, 50, 65, 80 mm
B - Overall width (mm)	121mm	125mm	150mm	165mm
S - Visible width (mm)	21mm	30mm	50mm	165mm
Accommodation of movement (mm)	5 (+/-2.5)	10mm (+/- 5mm)	14mm (+/- 7mm)	20mm (+/- 10mm)
Material	Aluminium & Nitriflex	Aluminium & Nitriflex	Aluminium & Nitriflex	Aluminium & Nitriflex
Load Bearing capacity (kN)	25kN	25kN		



Movement Joints (UK) Ltd,
Unit 3, 57 Thorby Avenue, March, Cambridgeshire PE15 0AZ United Kingdom
Tel: 01354 60 79 60 Fax: 01354 60 78 33
Web: www.mjuk.co.uk e-mail: info@mjuk.co.uk

IMPORTANT: Whilst all reasonable care is taken in compiling technical data on the company's products, all recommendations or suggestions regarding the use of such products are made without guarantee since the conditions of use are beyond the company. It is the customers responsibility to satisfy himself that each product is fit for the purpose for which he intends to use it and that the actual conditions of use are suitable.