


446/N SERIES


Surface fixed floor profile
 For use in
 hospitals • airports • shopping centres • schools

Features:

- Attractive finish
- Suitable for post fix installation
- aluminium construction with Nitriflex rubber insert
- Insert colours: black or grey. Alternative RAL coloured inserts are available - minimum order quantity applies.
- Smooth insert option available for laboratories and hospital wards (note: smooth insert reduces movement, contact us for further details).
- Options of a raised insert for use with vinyl or carpet to give a 'hidden' appearance
- Standard 4 metre lengths
- Floor to wall options
- Medium to heavy duty version 446/Nv series available














Floor to wall options available



Optional: raised inserts of 3mm for use with vinyl, or 5mm for carpet floor covering, see 446/Tn (3) and 446/Tn (5) data sheets

Note: smooth insert/seal options available for clean rooms, with reduced movement rating. Profiles are specified with suffix 'S' after code e.g. 446/N-030 (3) S Grey Insert.

Profile reference	446/N-020	446/N-030	446/N-050	446/N-065	446/N-100
Fb - Joint widths upto (mm)	20mm	30mm	50mm	65mm	100mm
H - Heights (mm)	17mm	26mm	26mm	26mm	30mm
B - Overall width (mm)	120mm	150mm	175mm	185mm	220mm
S - Visible width (mm)	120mm	150mm	175mm	185mm	220mm
Accommodation of movement (mm)	5 (+/-2.5mm)	10mm (+/- 5mm)	14mm (+/- 7mm)	20mm (+/- 10mm)	30mm (+/- 15mm)
Material	Aluminium & Nitriflex	Aluminium & Nitriflex	Aluminium & Nitriflex	Aluminium & Nitriflex	Aluminium & Nitriflex
Load Bearing capacity (kN)	 	 	 	 	 



Movement Joints (UK) Ltd,
 Unit 3, 57 Thorby Avenue, March, Cambridgeshire PE15 0AZ United Kingdom
 Tel: 01354 60 79 60 Fax: 01354 60 78 33
 Web: www.mjuk.co.uk e-mail: info@mjuk.co.uk

IMPORTANT: Whilst all reasonable care is taken in compiling technical data on the company's products, all recommendations or suggestions regarding the use of such products are made without guarantee since the conditions of use are beyond the company. It is the customers responsibility to satisfy himself that each product is fit for the purpose for which he intends to use it and that the actual conditions of use are suitable.