


Movement Joints (UK) Ltd

P O Box 10, Wisbech, Cambridgeshire PE13 4AN
 Tel: 01945 450736 Fax: 01945 450819
 Web: www.mjuk.co.uk
 e-mail: info@mjuk.co.uk

497/ AL + ALE series

Field Limitation Joints



Floor to wall profiles available

Profile Number	497/AL	497/ALE
Fb - Joint widths up to (mm)	12	12
H - Heights (mm)	50/60	50/60
B - Overall width (mm)	212	212
S - Visible width (mm)	15	17
Accommodation of movement (mm)	5 (+/- 2.5)	5 (+/- 2.5)
Colours	black, grey	
Material	aluminium, Nitriflex®, PVC	aluminium, Nitriflex®, PVC, stainless steel
Standard Length (metres)	4	
Load Bearing capacity (kN)		

Applications:

For all finishes (Screed, natural stone, cast stone etc)

Profile characteristics:

Smooth interchangeable insert, separation of mortar bed by means of an adjustable central section.

IMPORTANT

Whilst all reasonable care is taken in compiling technical data on the company's products, all recommendations or suggestions regarding the use of such products are made without guarantee since the conditions of use are beyond the company. It is the customers responsibility to satisfy himself that each product is fit for the purpose for which he intends to use it and that the actual conditions of use are suitable.

