

Movement Joints (UK) Ltd

P O Box 10, Wisbech, Cambridgeshire PE13 4AN
 Tel: 01945 450736 Fax: 01945 450819
 Web: www.mjuk.co.uk
 e-mail: info@mjuk.co.uk

710 Series


Field Limitation Joints
 For hard floor finishes



710 series



710/E series



710/B series

Profile Number	710-AL/VA/MS	710/E-AL/VA/MS	710/B-AL/VA/MS
Fb - Joint widths up to (mm)	10	10	10
H - Heights (mm)	20/ 25 / 30 / 40 / 50 / 60		
B - Overall width (mm)	14	40	70
S - Visible width (mm)	14 (also available as 9mm)		
Accommodation of movement (mm)	2 (+/-1)		
Colours	Black, grey and RAL colours		
Material	AL = Aluminium, VA = Stainless steel Nitriflex®		MS = Brass
Standard Length (metres)	3	3	2.5
Load Bearing capacity (kN)			

Applications:

For all finishes (Screed, natural stone, cast stone etc)

Profile characteristics:

Easy to install, high abrasion resistance, high load bearing capacity.
 Alternative heights from 10mm available

IMPORTANT

Whilst all reasonable care is taken in compiling technical data on the company's products, all recommendations or suggestions regarding the use of such products are made without guarantee since the conditions of use are beyond the company. It is the customers responsibility to satisfy himself that each product is fit for the purpose for which he intends to use it and that the actual conditions of use are suitable.

